

Kleensteam CT #9797-50 (countertop steamer) - 1.67 gpm max. flow
and Kleensteam II #9797-21 System - 2.5 gpm max. flow

- A total system delivering high quality filtered water with scale inhibition and deliming capabilities
- Kleensteam II, dual cartridge design for enhanced performance for high capacity steamers
- Filters water to improve performance, maximize energy efficiency and steam equipment life
- Reduces chlorine-induced corrosion
- Taste and odor reduction
- Cyst, Turbidity and TDS Reduction
- Simple to install, operate and maintain
- Long lasting IMF-10 cartridge delivers scale inhibitor
- Easy deliming with ScaleKleen through SR-X bowl



Colddrink 3-MC² #9328-06 and QC71 Quad-MC² #9437-10
27,000 gallons Capacity 36,000 gallons Capacity
5.0 gpm max. flow 6.7 gpm max. flow

- One system provides premium quality water to high flow fountain dispensers, coffee makers and ice machines
- New and improved Micro-Pure II media inhibits the growth of bacteria
- Reduces chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages
- Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces health contaminants such as cysts
- Increases the overall efficiency of equipment
- 20" prefilter captures larger dirt particles
- SR-X with SS-IMF cartridge inhibits scale buildup in ice machines and coffee brewers
- Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination
- NSF Certified under NSF/ANSI Standards 42 and 53





Water Filtration Made Easy!

7SO Softening Cartridge # 9607-04

Softening cartridge reduces scale-forming minerals

- Softening cartridge reduces scale forming minerals like calcium and magnesium in hard water situations
- May be used on water having up to 30 grains hardness per gallon at flow rates of up to ½ gallons per minute
- Sanitary quick change cartridge makes replacement easy
- Should be used with an Everpure fine filter cartridge installed in a series plumbed twin head.
- Capacity 2,000 grains
- Maximum Flow 0.5 gpm



MRS-20 Reverse Osmosis System # 9797-91

Complete Mineral Reduction Water Processing System

- Improves equipment life and performance by removing at least 90%+ of all dissolved solids that cause scale build-up
- Protects against taste and odor causing contaminants while removing dirt, particles and dissolved minerals
- Less frequent deliming of equipment means reduced maintenance and service costs
- Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination
- Two-part design makes installation flexible, and small footprint easily fits in any kitchen
- Easy to operate system has no moving parts and requires no electrical power
- System includes mineral reduction processor, carbon filter cartridge, reverse osmosis cartridge, and storage tank
- No monitoring of grains per gallons is necessary. System removes scale reducing minerals regardless of the grams per gallon (GPG)

